



## Zero Gravity Filters Pneumatic Phoenix

### SPECIFICATION SHEET

Filter System	
Filter Element	Stainless steel 316L with stainless steel 316 cage assemblies
Filter Body	Stainless steel 304L.
Indexing Valve	Stainless steel 304 with polyacetal shoe.
Indexing Actuator	Double acting, developing 150 Lb Ins at 80 psi. Manufactured by Bray Valve and Controls, series 90, size 48.
Proximity Switch	Inductive proximity switch. Manufactured by Efector, Inc.
Dog Clutches	Hardened nickel bronze casting.
Backwash Valve	3/4" stainless steel 316 ball valve, stainless steel ball and PTFE seals and RPTFE seats.
Backwash Valve Actuator	Double acting, developing 199 in/lb at 80 psi. Manufactured by Assured Automation, size PD030.
Connections	Inlet and outlet are 3" stainless steel 304 ANSI raised faced 150# flanges. Backwash connection is 3/4" NPT female.
O-rings and seats	Viton standard.

Controls	
Enclosure	Coated steel to NEMA 4 standard, exterior painted (RAL 5013, ZGF Blue)
Logic Module	Siemens LOGO 24RCL, UL Approved.
Panel Supply	Siemens 24 VDC, 1.3 Amp transformer, UL Approved.
Air Valve Manifold	Parker B3 series modular manifold with 24 VDC solenoid valves, UL approved.
Pressure Transducers	1/4" connection, stainless steel 316 housing. IP 67 protection. 4...20mA analog output.

**Pneumatic Phoenix**

**Specification Sheet**

Operating Parameters	
Number of Elements	6 per unit.
Flowrate (Based on clean differential pressure of less than 3 psi)	35 gpm (132 LPM) minimum, 250 gpm (946 LPM) maximum per Phoenix. 20µ: 60 gpm, 35µ: 110 gpm, 50µ: 150 gpm, 75µ: 180 gpm, 100-400µ: 250 gpm. Note: Maximum solids loading not to exceed 500 ppm.
Operating Pressures	120 psi (827 kPa) maximum, 230 psi (1,586 kPa) test pressure. Minimum of 35 psi on filter's discharge during backwash. Maximum differential pressure of 50 psi
Operating Temperature	190°F (88°C) maximum.
Micron Ratings	20, 35, 50, 75, 100, 150, 200 and 400 micron absolute gap.
Backwash Control	Automatically using interval timer and/or differential pressure or manually using push button.
Energy Consumption (per backwash)	Air: 14 cubic inches Electrical: 15 watts
Approximate Backwash Volume	5 gallons

Site Requirements	
Air Supply	60 to 80 psi, clean and dry. Air line connection on bottom of control panel is ¼" OD push-in bulkhead fitting.
Electrical Supply	120 or 240 VAC, 5 amps
Outputs	Volt free contacts (normally open), maximum 2 amps
Pneumatic Pipework	5/32" pneumatic flexible tubing with push-in connectors
Approximate Dimensions and Weight	22 x 16 x 17" (55 x 40 x 44 cms) Dry: 75 lbs, Wet: 109 lbs (34 kgs, 49.4 kgs)
Fluid Volume	4.1 Gallons

Materials	Standard	Upgrade	Upgrade
Control Panel Enclosure	Carbon Steel, NEMA 4	NEMA 4X	Custom Color
Backwash Valve Actuator	Double Acting	Spring Return	
Filter Elements – Holder	30% Glass Filled Polypropylene	SS304	SS316
O-rings	Viton	Buna, EPDM	Options
Valve Seats	RPTFE	Options	

Revision D, January 2019.

**U.S.A. Headquarters**  
12300 Emerson Drive  
Brighton, MI 48116

**Phone** 248-486-3500  
**Fax** 248-486-3501

**Email** info@zgfilters.com  
**Web** zgfilters.com